

AD-here® 260L

Technical Data Sheet	
Description	AD-here® 260L is an amidoamine based asphalt adhesion agent. It is an excellent choice for patching or stockpile/depot mixtures. It greatly increases the adhesion of asphalt to wet or dry aggregate and reduces the potential for moisture damage. It will improve the coating and workability of the mixture and increase its adhesion to the pothole.
Typical Properties	Appearance: Dark Brown Liquid Viscosity, 25°C: 300 cps Specific Gravity, 25°C: 0.94 Flash Point (P.M.C.C.): > 93°C
Features	N/A
Applications	AD-here® 260L is added to asphalt in the amount of 0.5 – 3.0% by weight of the asphalt, depending on the asphalt and aggregate type. It substantially increases the level of wet aggregate coating as compared to untreated mixes. AD-here® 260L is also used as a dispersing and coating additive for coal tar emulsions.
Packaging	N/A
Storage and Handling	Refer to MSDS prior to handling this material. Avoid water contamination during handling and storing. AD-here® 260L is available in bulk quantities and in 200-liter non-returnable drums (190 kg net). It is available from our manufacturing location in Mulberry, Florida.
TSCA Compliance	N/A

All suggestions and data are based on information and tests we believe to be reliable. Insofar as applications by prospective users may differ from those recommended, it is suggested the user conduct tests and determine the suitability of the product to his process. No warranty for the application of this product is expressed or implied.