

## AD-here® CB

Technical Data Sheet	
Description	AD-here® CB is an adhesion promoter for asphalt cements, cutbacks, emulsions and coal tar. It greatly increases the adhesion of asphalt to wet or dry aggregate and as an additional benefit, provides resistance of the mixture to moisture damage.
Typical Properties	Appearance: Dark Brown Viscous Liquid Viscosity: 77°F 4000 cps Viscosity: 100°F 400 cps Density, Pounds/Gallon :77°F 7.95 Flash Point (P.M.C.C.): > 300° F
Features	N/A
Applications	AD-here® CB is added to asphalt in the amount of 0.5 - 2.0% by weight of the asphalt cement, depending on the asphalt and aggregate type. It substantially increases the level of wet aggregate coating as compared to untreated mixes. AD-here® CB is an excellent dispersing and coating agent for coal tar sealers.
Packaging	AD-here® CB is available in bulk quantities (1000 - 5500 gal.) and in 55-gallon non-returnable drums (420 net pounds). It is available from our manufacturing location in Mulberry, Florida.
Storage and Handling	Refer to MSDS prior to handling this material. Avoid water contamination during handling and storing. For ease of pumping it is recommended to keep the product at 100° - 130°F.
TSCA Compliance	N/A

All suggestions and data are based on information and tests we believe to be reliable. Insofar as applications by prospective users may differ from those recommended, it is suggested the user conduct tests and determine the suitability of the product to his process. No warranty for the application of this product is expressed or implied.