

Safety-Solv 140 Plus

Technical Data Sheet	
Description	Safety-Solv 140 PLUS is a biodegradable, non-chlorinated solvent used to extract asphalt cement from bituminous mixes. Safety-Solv 140 PLUS is a clear liquid having an odor similar to that of pine oil. This product contains terpene hydrocarbons and proprietary emulsifiers.
Typical Properties	Appearance: Clear Liquid Viscosity, 77°F: 15 cps Density, Pounds/Gallon, 77°F: 7.2 Flash Point (P.M.C.C.): > 140°F
Features	<ul style="list-style-type: none"> • Non-hazardous and biodegradable. • Rinses easily with water. • Excellent degreaser and asphalt cleaner.
Applications	Safety-Solv 140 PLUS can be used in both the centrifuge and vacuum extraction methods for asphalt content determination. Safety-Solv 140 PLUS can replace the use of hazardous trichloroethylene and trichloroethane.
Packaging	Safety-Solv 140 PLUS is available in 55 gallon non-returnable drums (385 lbs. net). It is available from our three manufacturing locations: Mulberry, Florida; Convent, Louisiana; and Vanceboro, North Carolina. WARNING: Combustible materials such as rags, paper, etc. that are soaked in Safety-Solv 140 PLUS should be disposed in fire-safe containers approved for combustible waste. DO NOT dispose in trash cans since spontaneous combustion may occur.
Storage and Handling	Refer to MSDS prior to handling this material.
TSCA Compliance	N/A

All suggestions and data are based on information and tests we believe to be reliable. Insofar as applications by prospective users may differ from those recommended, it is suggested the user conduct tests and determine the suitability of the product to his process. No warranty for the application of this product is expressed or implied. arising from this transaction or the product, Buyer's remedy shall be limited to replacement of the product, or the purchase price, solely in AMCC's discretion, and Buyer waives any and all other types of damages, including but not limited to incidental, consequential, special or other damages.